



# BEST OF LIME

INNOVATORS IN LIME PLASTERS

## Declaration of Performance

# UK CA

Unit A, Homefield Road, Haverhill, Suffolk, CB9 8QP

## Limecote

Dry Bagged non-hydraulic Insulating Lime Plaster for use internally or externally  
Supplied in 25kg LDPE packaging

|   |                              |  |
|---|------------------------------|--|
| Reaction to Fire:                         | Class A1                     | EN ISO 1716: 2018<br>EN ISO 1182: 2020 |
| Dry Bulk Density                          | 1,200kg/m <sup>3</sup>       |  |
| Colour                                    | Off-White                    |  |
| Water Vapour Permeability Coefficient     | 2.66 Kg/m <sup>2</sup> .s.Pa | BS EN 1015-19: 1999                    |
| 28 Day Compressive Strength               | 1.4 N/mm <sup>2</sup>        | BS EN 1015-11: 2019                    |
| 28 Day Flexural Strength                  | 1.0 N/mm <sup>2</sup>        | BS EN 1015-11: 2019                    |
| Mean Thermal Conductivity $\lambda$ (Dry) | 0.330 W/(m.k)                | BS EN 1745: 2020                       |

The performance of the product identified above (Warmcote) is in conformity with the declared standards and in accordance with:

THE MINISTRY OF HOUSING, COMMUNITIES & LOCAL GOVERNMENT NOTICE OF PUBLICATION  
0035/21 of 1 January 2021

Of references to standards for construction products in support of Regulation (EU) No 305/2011 as amended by The Construction Products (Amendment etc.) (EU Exit) Regulations 2019 (S.I. 2019/465)

Date 07/11/2022

Signed

Martin Brown, Director.