



BEST OF LIME

INNOVATORS IN LIME PLASTERS

Declaration of Performance

UK CA

Unit A, Homefield Road, Haverhill, Suffolk, CB9 8QP

Warmcote

Dry Bagged non-hydraulic Insulating Lime Plaster for use internally or externally
Supplied in 25kg LDPE packaging

Reaction to Fire:	Class A1	EN ISO 1716: 2018 EN ISO 1182: 2020
Dry Bulk Density	625kg/m ³	
Colour	Off-White	
Water Vapour Permeability Coefficient	1.302 Kg/m ² .s.Pa	BS EN 1015-19: 1999
28 Day Compressive Strength	1.6 N/mm ²	BS EN 1015-11: 2019
28 Day Flexural Strength	0.7 N/mm ²	BS EN 1015-11: 2019
Mean Thermal Conductivity λ (Dry)	0.140 W/(m.k)	BS EN 1745: 2020

The performance of the product identified above (Warmcote) is in conformity with the declared standards and in accordance with:

THE MINISTRY OF HOUSING, COMMUNITIES & LOCAL GOVERNMENT NOTICE OF PUBLICATION
0035/21 of 1 January 2021

Of references to standards for construction products in support of Regulation (EU) No 305/2011 as amended by The Construction Products (Amendment etc.) (EU Exit) Regulations 2019 (S.I. 2019/465)

Date 07/11/2022

Signed

Martin Brown, Director.